L-PCM06B 6.5" METAL CEILING LOUDSPEAKER WITH METAL DOME

- Clear and stereo audio performance
- Cone edge with damp glue for longer operation life
- Sturdy press fit metal grille appearance
- Simple power setting
- Flush-mounting system for fast and easy installation
- CE and RoHS complied



PRODUCT DESCRIPTION

L-PCM06B is a cost-competitive ceiling loudspeaker which has an excellent audio performance and a esthetic appealing enclosure. Its low-profile, white color design blends easily most interiors in locations such as hotels, warehouses, schools, office buildings, stadiums and restaurants. This full rang loudspeaker features a high sound pressure level and a wide frequency


response range. It has a built-in 6W integrative-cone speaker and a 100V matching transformer mounted back dome, Supplied with a metal back dome, the components inside are well protected in case of emergency. It is CE and RoHS complied.

Technical Specification	
Max power	9 W
Rated power	6 W
Power taps @ 100V	6 W/3W/1.5 W
SPL at 6W / 1W (150Hz-20kHz, 1m)	100 dB/92 dB
Frequency response (-10dB)	110 Hz - 20 KHz
Dispersion angle (1 KHz/-6 dB)	180°
Rated input voltage	100 V / 70 V


Rated impedance	1.7kΩ /3.3kΩ /6.7KΩ
Connector	Push-in terminal block
Dimensions (Φ × H)	Φ 200 × 100 mm
Hole cut-out size	Φ175mm
Weight	1.08 Kg
Color	White RAL 9003)
Speaker size	6.5*
Operating temperature	-25 °C to + 55 °C
Storage temperature $-40 ^{\circ}\mathrm{C}$ to + 70 $^{\circ}\mathrm{C}$	
Relative humidity	< 95 %




Frequency Response:




Circuit Diagram:



Polar Diagram



Three View Diagram



For more information,

https://honeywellbuildings.in Call: 1-800-103-0339 Email: HBT-Indiabuildings@honeywell.com

Honeywell HBT India Buildings

Unitech Trade Center, 5th Floor, Sector-43, Block C, Sushant Lok Phase - I, Gurgaon - 122 002 CEILING LOUDSPEAKER WITH METAL DOME

Honeywell